

Application No. 10/521685  
Reply to Action dated August 7, 2008

RECEIVED  
CENTRAL FAX CENTER  
FEB 06 2009

### IN THE CLAIMS

#### Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. (Currently Amended) An analyzing device, comprising:  
a rotating body for transferring a target analyte; [[,]]  
an optical detector for optically analyzing the target analyte;  
wherein the rotating body holding holds the target analyte by applying a negative  
pressure to the target analyte while transferring the target analyte in a circumferential direction of  
the rotating body; [[,]]  
wherein the rotating body including includes an inner space for negative pressure  
application, a plurality of positioning portions, each for placing and holding the target analyte,  
and through-holes for connecting the positioning portions and the inner space; [[,]] and  
wherein the inner space accommodating accommodates a blockade member for  
selectively closing or opening the through-holes by movement relative to the rotating body.
2. (Canceled)
3. (Previously Presented) The analyzing device according to claim 1, further comprising a negative pressure generator for applying the negative pressure to the inner space.
4. (Original) The analyzing device according to claim 1, wherein the rotating body includes a rotary axis extending insubstantially horizontal direction.
5. (Previously Presented) The analyzing device according to claim 1, wherein the rotating body is formed as a cylinder having an outer surface formed with the positioning portions.

Application No. 10/521685

Reply to Action dated August 7, 2008

6. (Original) The analyzing device according to claim 5, wherein the positioning portions extend in an axial direction of the rotating body and are spaced from each other in a circumferential direction of the rotating body.
7. (Canceled)
8. (Previously Presented) The analyzing device according to claim 1, wherein the blockade member extends in an axial direction of the rotating body and is formed with a cutout extending in the axial direction.
9. (Previously Presented) The analyzing device according to claim 1, further comprising a housing for accommodating at least a part of the rotating body, wherein one end of the blockade member is non-rotatably supported by the housing.
10. (Currently Amended) The analyzing device according to claim 1, ~~further comprising an optical detector for optically analyzing the target analyte~~, wherein the blockade member opens the through-hole connected to the positioning portion on which the target analyte is placed when the ~~[[the]]~~ target analyte assumes a position for measurement by the optical detector, thereby applying the negative pressure on the target analyte.
11. (Original) The analyzing device according to claim 10, wherein the target analyte is transferred by rotating the rotating body through no less 180 degrees, the target analyte being transferred from a position at which the target analyte is placed at the positioning portion to the position for measurement by the optical detector.
12. (Previously Presented) The analyzing device according to claim 1, wherein the blockade member closes the through-hole connected to the positioning portion at a position where the target analyte is placed on the positioning portion, thereby preventing the target analyte from being subjected to the negative pressure.
13. (Original) The analyzing device according to claim 1, further comprising a blade for

Application No. 10/521685  
Reply to Action dated August 7, 2008

removing the target analyte held on the positioning portion.

14. (Original) The analyzing device according to claim 13, wherein the rotating body is provided with a guide portion for allowing the blade to move relative to the rotating body in intimate contact therewith.

15. (Previously Presented) The analyzing device according to claim 1 wherein a suction applying clearance is provided between each positioning portion and the through-hole connected to the positioning portion, the suction applying clearance applying the negative pressure on the target analyte in an area extending in an axial direction of the rotating body.

16. (Previously Presented) The analyzing device according to claim 15, wherein the suction applying clearance is formed by forming a recess smaller than each positioning portion adjacent to a disposing portion and closer to an axis of the rotating body.

17. (Original) The analyzing device according to claim 1, wherein the target analyte is an analyzing tool for analyzing a sample, an excess of the sample adhering to the analyzing tool being removed when the analyzing tool is subjected to the negative pressure.

18-20. (Canceled)